AKUSTUS DESIGNS WALL PANELS INFO@AKUSTUS.COM AKUSTUS.COM

Metro Wall Panels



METRO




Methodical curves and parallel lines come together in the Metro Wall Panel. Like a complex train system, Metro's intricate network whisks you away to see the sights while cutting out the noise.

WALL PANELS

How to Specify


Step by step instructions on how to specify Metro Wall Panels.



01

Choose a thickness.

(pg 03)




02

Option A

Choose a panel design and create your own configuration.

Option B

Choose one of our configurations. (pg 04-05)




03

METRO

Choose a standard colour or a set from our Impressio Colourways.

(pg 06-10)



04 Choose an installation

method. (pg 11)

Dimensions

Standard Dimensions (mm)

600 W x 600 H

Standard Thicknesses (mm)

12, 18 and 24


Edge Detail



Bevel Edge


Customization

Panel Width and Height can be adjusted to fit your space.



Panel Designs


The building blocks of the Metro Wall Panel.




05 METRO WALL PANELS AKUSTUS.COM

Configurations


Mix and match panel designs to make the wall your own, or choose from one of our suggestions.




Config A




Config D




Config B



Config E



Config C



Config F

Customization

your space.

Metro is designed for customization. Ask us about changing the panel design, configuration or colour to fit

Impressio Colourways are unique colours curated for Metro. Each set complements the design and allows the twists and turns of the panels to shine through.


Colourways can be specified in either one-colour, two-colour or multi-colour sets.

Vancouver **New York** VA 02 VA 01 VA 03 VA 04 NY 01 NY 02 NY 03 NY 04 Sao Paulo Madrid MA 01 MA 02 MA 03 MA 04 SA 01 SA 02 SA 03 SA 04 Seoul Dubai






One-Colour




Config A in SA 03.




Config D in SE 03.




Config A in MA 01.



Config E in NY 02.




Config B in NY 04.



Config E in VA 01.




Config C in DU 03.




Config F in SA 01.


Two-Colour




Config A in Madrid Colorways.




Config C in New York Colorways.




Config A in Dubai Colorways.




Config E in Vancouver Colorways.




Config B in Vancouver Colorways.



Config E in Sao Paulo Colorways.




Config B in Vancouver Colorways.




Config F in Seoul Colorways.




Multi-Colour




Config C in Seoul Colorways.




Config D in Madrid Colorways.




Config C in Dubai Colorways.




Config D in Vancouver Colorways.




Config E in Vancouver Colorways.



Config F in Dubai Colorways.



Config E in New York Colorways.



Config F in Sao Paulo Colorways.

Standard Colours

Choose from any one of our standard colours.

Don't see something you love? Ask us about creating your own custom colour.

All colours available in 9, 12, 18 and 24 mm unless noted otherwise.


* 12 mm / 24 mm only




Installation & Hardware

This is an overview of the available installation methods. Check out our installation guide for more details.

Construction Adhesive




Push Mount Clips




WALL PANELS

AKUSTUS.COM

Z-Clips



Concealed Mechanical Fasteners



12

Product Specifications

Metro Wall Panels

Composition

100% polyester fibre

VOC Emissions

CDPH (CA 01350)

Antimicrobial Testing

Mould & mildew resistant

Fire Rating

- ASTM E84 Class A
- CAN/ULC-S102.2-10



AKUSTUS

Sustainability


- 100% recyclable
- LBC Red List free
- Contributes to LEED certification
- Free of toxic substances and of off-gassing
- Made with ~60% recycled content from plastic water bottles

Colour & Texture Variations

The felting and dyeing process that forms the material contributes to its unique texture but also to variations in texture and colour from panel to panel. Products will be provided within an acceptable range of variation.

Sound Absorption Graph

The following values reflect the acoustic properties of the product as tested in accordance with ASTM C423-09a.



	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	NRC	SAA
12 mm	0.04	0.09	0.13	0.15	0.28	0.38	0.48	0.54	0.58	0.66	0.73	0.65	0.40	0.39
18 mm	0.10	0.12	0.18	0.30	0.44	0.63	0.72	0.81	0.87	0.91	0.94	0.97	0.60	0.58
24 mm	0.14	0.24	0.29	0.41	0.69	0.80	0.87	0.94	0.96	0.94	0.88	0.86	0.70	0.67

Product Care

Handling & Storage

Handle products with care so as to avoid folding the polyester felt, chipping its edges or indenting its faces. Store products in their original containers in a well-ventilated area until the intended application environment is ready for installation. Allow products to acclimatize to environmental conditions. Lay them flat on their faces; do not stand them on their edges. Protect from moisture, heat, direct sunlight and the elements.

Warranty

AKUSTUS warrants the construction and finish of all our products to be free from defects in material and workmanship for a period of 1 year from the date of purchase.

Maintenance

Lightly brush or gently vacuum to remove dust from polyester felt.
Clean with warm water and mild, non-toxic soap to remove spills. Test solution on an inconspicuous spot before applying to more visible areas. Blot with a dry cloth after applying the solution to avoid saturating the material. Avoid applying too much pressure when cleaning the products.

