

AKUSTUS DESIGNS INFO@AKUSTUS.COM AKUSTUS.COM AKUSTUS.COM

Madera 3D Panels








Madera, the Spanish word for "wood", embodies the warmth and character of its namesake while silently doing away with noise.

How to Specify

Step by step instructions on how to specify <u>Madera</u> <u>3D Panels</u>.







01

Choose panel design. (pg 04)

Choose colour. (pg 05-09)

02

Choose installation method. (pg 10)

03

MADERA 3D PANELS AKUSTUS.COM

Dimensions

Standard Dimensions (mm)

610 W x 2745 H

Standard Thickness (mm)

22

Slat Width (mm)

27, 37, 44

Slat Reveal (mm)

24


Edge Detail



Square Edge

Customization

Width and Height can be customized to fit your space.




610 mm (24 in)

04 MADERA 3D PANELS AKUSTUS.COM

Panel Designs

Madera comes in 3 standard designs which feature different slat widths.



Customization

Slat width and depth can be customized to your liking.




Colour Options Textures

Madera pairs perfectly with woodgrain. Choose a texture for the slats and a standard colour for the base.

Customization


Have a woodgrain you want to match? Ask us about creating your own custom woodgrain.

See all textures on pg 08.



Colour Options Standard Colours

Mix and match standard colours to create your dream combination.




See all standard colours on pg 09.




Colour Options Graphics

Get inspired by our curated graphics.


Graphic A




Graphic B



Graphic C



Graphic D



Customization

Have an image you want to use? Ask us about creating your own custom graphic. 08 MADERA 3D PANELS AKUSTUS.COM

Textures

Create a natural look and feel with printed textures.








Silver Oak



Greige Oak



Ebony Oak





Cafe Oak



Golden Oak



Teak



Walnut


Standard Colours

Choose from any one of our standard colours.

Don't see something you love? Ask us about creating your own custom colour.

* Available in 12 / 24 mm only. All other colours available in 9, 12, 18, and 24 mm.

Pure White Urban Grey Pumice Warm Grey SP 07 SP 79 SP 11 **Almond** Beige Sandstone Ivory SP 77 SP 91 SP 04 Sunflower Mustard* Orange SP 05 SP 87 SP 46 Pistachio* Olive* Chartreuse SP 95 SP 43 SP 88 Aquamarine Pale Teal Lagoon* SP 73 SP 74 SP 84



Cool Grey

SP 36

Taupe Grey

SP 90

SP 76

SP 12

Mid Grey

SP 37

Castlerock*

SP 80

Graphite

SP 03

Yam

SP 28

Black

SP 13


Tangerine*

SP 92


Installation

This is an overview of the available installation methods. Check out our installation guide for more details.


Construction Adhesive



Concealed Mechanical Fasteners



Z-Clips



11

Product Specifications

Madera 3D Panels

Composition

100% polyester fibre

Health & Safety

- Fire-rated
- ASTM E84 Class A
- CAN/ULC-S102.2-10 compliant
- Low VOCs
- CDPH v1.2 compliant
- Mould & mildew resistant
- ASTM C1338 compliant

Colour & Texture Variations

The felting and dyeing process that forms the material contributes to its unique texture but also to variations in texture and colour from panel to panel. Products will be provided within an acceptable range of variation.

Sustainability

- 100% recyclable
- Made with 60% post consumer recycled content
- Declare Red List free
- Contributes to LEED certification
- Environmental Product Declaration








Sound Absorption Graph The following values reflect the acoustic properties of the

The following values reflect the acoustic properties of the product as tested in accordance with ASTM C423-09a.



		200	250	315	400	500	630	800	1000	1250	1600	2000	2500	NRC	SAA
M	ladera A	0.07	0.09	0.18	0.24	0.36	0.53	0.69	0.80	0.92	1.00	1.02	1.06	0.55	0.58
N	ladera B	0.06	0.07	0.18	0.25	0.39	0.54	0.72	0.83	0.93	0.99	1.02	1.07	0.60	0.59
M	ladera C	0.07	0.11	0.22	0.27	0.42	0.60	0.76	0.87	0.96	1.03	1.03	1.08	0.60	0.62



Handling & Storage

Handle products with care so as to avoid folding the polyester felt, chipping its edges, or indenting its faces. Store products in their original containers in a well-ventilated area until the intended application environment is ready for installation. Allow products to acclimatize to environmental conditions. Lay them flat on their faces; do not stand them on their edges. Protect from moisture, heat, direct sunlight, and the elements.

Warranty

AKUSTUS warrants the construction and finish of all our products to be free from defects in material and workmanship for a period of 1 year from the date of purchase.

Maintenance

Lightly brush or gently vacuum to remove dust from polyester felt.
Clean with warm water and mild, non-toxic soap to remove spills. Test solution on an inconspicuous spot before applying to more visible areas. Blot with a dry cloth after applying the solution to avoid saturating the material. Avoid applying too much pressure when cleaning the products.

