



Stripes Ceiling Tile

BY AKUSTUS DESIGNS

AKUSTUS

®

[AKUSTUS.COM](https://akustus.com)

[INFO@AKUSTUS.COM](mailto:info@akustus.com)



STRIPES CEILING TILE

STR-CT-BB-060-060 & STR-CT-BC-060-121

Stripes Ceiling Tiles showcase the timeless appeal of simple patterns formed by parallel lines. Where most ceiling tiles are made with only acoustic benefits in mind, these tiles are fashioned to provide aesthetic appeal as well. Flat and flush with the ceiling or protruding from the ceiling in the shape of a box, these tiles can be placed in a ceiling grid system to transform an office in the middle of downtown or a store in the middle of a shopping mall.

STRIPES CEILING TILE





STR-CT-FB-060-060 & STR-CT-FC-060-121

Dimensions - Flat Ceiling Tile

Available Thicknesses: 18 mm (0.7 in)

* Custom size available.




Product Data

Product Code	Width x Length	Thickness	Weight
STR-CT-FA-060-060	605 x 605 mm 23.8 x 23.8 in	18 mm 0.7 in	1.5 kg 3.3 lb
STR-CT-FA-060-121	605 x 1215 mm 23.8 x 47.8 in	18 mm 0.7 in	2.9 kg 6.4 lb
STR-CT-FB-060-060	605 x 605 mm 23.8 x 23.8 in	18 mm 0.7 in	1.5 kg 3.3 lb
STR-CT-FB-060-121	605 x 1215 mm 23.8 x 47.8 in	18 mm 0.7 in	2.9 kg 6.4 lb
STR-CT-FC-060-121	605 x 1215 mm 23.8 x 47.8 in	18 mm 0.7 in	2.9 kg 6.4 lb


Dimensions - Box Ceiling Tile

Available Thicknesses: 50, 75, 100, 150 mm (2, 3, 3.9, 5.9 in)

* Custom size available.



STRIPES CEILING TILE



Product Data

Product Code	Width x Length	Thickness	Weight
STR-CT-BA-060-060	605 x 605 mm 23.8 x 23.8 in	50, 75, 100, 150 mm 2, 3, 3.9, 5.9 in	1, 1.1, 1.2, 1.5 kg 2.2, 2.4, 2.6, 3.3 lb
STR-CT-BA-060-121	605 x 1215 mm 23.8 x 47.8 in	50, 75, 100, 150 mm 2, 3, 3.9, 5.9 in	1.8, 2, 2.2, 2.6 kg 4, 4.4, 4.9, 5.7 lb
STR-CT-BB-060-060	605 x 605 mm 23.8 x 23.8 in	50, 75, 100, 150 mm 2, 3, 3.9, 5.9 in	1, 1.1, 1.2, 1.5 kg 2.2, 2.4, 2.6, 3.3 lb
STR-CT-BB-060-121	605 x 1215 mm 23.8 x 47.8 in	50, 75, 100, 150 mm 2, 3, 3.9, 5.9 in	1.8, 2, 2.2, 2.6 kg 4, 4.4, 4.9, 5.7 lb
STR-CT-BC-060-121	605 x 1215 mm 23.8 x 47.8 in	50, 75, 100, 150 mm 2, 3, 3.9, 5.9 in	1.8, 2, 2.2, 2.6 kg 4, 4.4, 4.9, 5.7 lb

STRIPES CEILING TILE


Specifications

Product Name	Stripes Ceiling Tile
Composition	100% polyester fibre
Edge Detail	Box / square edge
Fire Rating	<ul style="list-style-type: none">ASTM E84 Class ACAN/ULC-S102.2-10
VOC Emissions	CDPH (CA 01350)
Antimicrobial Testing	Mould & mildew resistant
Sustainability	<ul style="list-style-type: none">100% recyclableLBC Red List freeContributes to LEED certificationFree of toxic substances and of off-gassingMade with ~60% recycled content from plastic water bottles
How to Specify	<ul style="list-style-type: none">Product Name & CodeDimensionsColourInstallation Method
Colour & Texture Variations	The felting and dyeing process that forms the material contributes to its unique texture but also to variations in texture and colour from panel to panel. Products will be provided within an acceptable range of variation.




Acoustic Properties

The following values reflect the acoustic properties of the product as tested in accordance with ASTM C423-09a using Type D-50 mounting.




Installation

Flat Ceiling Tile



Box Ceiling Tile with Edge



Product Care

Handling & Storage

Handle products with care so as to avoid folding the polyester felt, chipping its edges or indenting its faces. Store products in their original containers in a well-ventilated area until the intended application environment is ready for installation. Allow products to acclimatize to environmental conditions. Lay them flat on their faces; do not stand them on their edges. Protect from moisture, heat, direct sunlight and the elements.

Maintenance

Lightly brush or gently vacuum to remove dust from polyester felt. Clean with warm water and mild, non-toxic soap to remove spills. Test solution on an inconspicuous spot before applying to more visible areas. Blot with a dry cloth after applying the solution to avoid saturating the material. Avoid applying too much pressure when cleaning the products.

Warranty






























AKUSTUS warrants the construction and finish of all our products to be free from defects in material and workmanship for a period of 1 year from the date of purchase.



STRIPES CEILING TILE

STR-CT-BB-060-060

Colours

 Pure White SP 07	 Krypton SP 30	 Urban Grey SP 79	 Pumice SP 11	 Warm Grey SP 76	 Cool Grey SP 36
 Ivory SP 77	 Beige SP 04	 Sandstone SP 12	 Mid Grey SP 37	 Graphite SP 03	 Black SP 13
 Orange SP 46	 Yam SP 28	 Wild Currant SP 48	 Plum SP 72	 Red SP 08	 Blush Pink SP 81
 Sunflower SP 05	 Chartreuse SP 43	 Desert Sage SP 78	 Green SP 10	 Forest Green SP 17	 Dark Turquoise SP 71
 Aquamarine SP 73	 Pale Teal SP 74	 Sky Blue SP 25	 Navy SP 01	 Midnight Blue SP 19	

NEW